



High Performance Bubble Free Digital Media for your Most Demanding Applications

## Graphics that Rock!



Wraps



Murals



Textures

MACtac®'s patented B•free™ air egress system makes your most demanding applications easy. Whether it is a rough textured wall or a vehicle wrap, MACtac's 5529 series is the right choice for your tough jobs.

## The Whole Enchilada

JT5500 Series B•free is available with two high performance adhesives. **JT5529BFD** is designed to be repositionable and easy to apply. **JT5529BFD Pro** has a high initial tack and develops an excellent bond quickly. It's ideal for experienced installers who need to turn their jobs fast.

## Where the Wrap Meets the Road

The 5529 B•free series is the most versatile wrap system in the industry. You can be confident that applications with B•free will provide you with significant competitive advantages.

- Patented omni-directional bubble free technology – squeegee in any direction and air pockets disappear.
- Optimized liner release for easier one-person installations with no vinyl distortion.
- Industry leading outdoor durability at ten years.
- Proprietary polymer facestock withstands heat better than cast vinyl, so wrinkles remove easily.
- Solvent, eco-solvent and screen printable. Industry's highest white point for the best image pop.
- Virtually no adhesive residue left behind at removal.
- With PERMACOLOR® RAYZor™ overlaminate, the most conformable wrap system from the industry.
- Add PERMACOLOR RAYZor matte or metallic Enhancers to your wrap arsenal for eye catching special effects.

Product	Gauge	Adhesive	Liner
JT5529BFD Pro	2.1 mil Soft gloss white	Permanent, Opaque Acrylic	80# Polycoated
JT5529BFD	2.1 mil Soft gloss white	Permanent, Opaque Acrylic	80# Polycoated

### Durability

- Long-term 10 year durability
- Use-life estimate based on accelerated age studies on vertical applications under "normal" environmental conditions.
- Severe environmental conditions will reduce use life.
- Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to MACtac® Product Performance Guides and Technical Assistance Bulletins prior to use. Visit [www.MACTac.com](http://www.MACTac.com) to download.

### Temperature Ranges

- Minimum Application: +50°F (+10°C)
- End Use: -58° to 194°F (-50° to 90°C)

### Shelf Life

Two years when stored at 60/77°F (15/25°C) and 50% relative humidity in the original package.



INTERNATIONAL SIGN ASSOCIATION

SERIOUSLY COOL TECHNOLOGY

